

Equipment

Designation	Drum size	Agitator rod length (mm)	Paddle diameter (mm)	cover diameter (mm)	Part number
COVER	20-40 L / 5-11 GI			400	154261600
40L AGITATOR	20-40 L / 5-11 GI	400	134		154261700
SUCTION	20-40 L / 5-11 GI				154261800
40l ram					151081000

Accessories

Designation	Part number
2 L.DRUM - OIL HP 150 FOR DIAPHRAGM PUMP & OILER	149990017
DRUM ROLLER PLATE 200 L ONLY	151098100
ARI SUPPLY ASSEMBLY	154261930
SLOTTED PADDLE	154261952
AIR FILTER 1/4	154261996
AIR LUBRICATOR 1/4 + SUPPORT	154261997

Cyclix 20-40

Drum Cover Agitators

Airspray / Accessories



AGITATION FOR BEST RESULTS

- Constant quality of mixed materials
- Stainless steel wetted parts
- High ROI - no product lost

Markets



BOND • PROTECT • BEAUTIFY



# Cyclix 20-40

## Drum Cover Agitators

Cyclix gear drive agitators for open top 20-40 liter drum feature a stainless steel cover mounted on a single post elevator for quick material changes.

This elevator-agitator for 20-40 drums features a double-effect jack for a fast lift of a stainless steel cover fitted for a quick material drum change. The cover is equipped with a motorized agitator fitted with blades for low viscosity materials and a full stainless steel rod. The elevator is coming on a large fixing plate which makes it very stable and easy to install in paint kitchens, existing installations or an essential component of new installations



### Technical data table


Designation	Value	Unit: metric (US)
Length	696 (27)	mm (in)
Height	1024-1500 (40-59)	mm (in)
Width	400 (15.7)	mm (in)
Recommended Fluid Pressure	60 (1.40)	bar (psi)
Rotation Speed	150	l/min (rpm)
Torque at 100 rpm	2.2	Nm
Maximum Air Consumption	43.2	m <sup>3</sup> /h (cfm)
Maximum Pressure	6.9 (100)	bar (psi)
Max power	0.75	kW
Stopping torque	2.1	Nm



### Technologies



Airmix® spray technology



Electrostatic



Airless spray technology



Airspray Conventional



### Description

#### Performance

- ◆ Bi-directional jack for fast lift of stainless steel agitator cover (3 positions available)
- ◆ Quick material change
- ◆ Lubricated air motor - compact with adjustable speed and safe operation

#### Productivity

- ◆ User-friendly
- ◆ Agitator disengaged during elevator movement

#### Sustainability

- ◆ Stainless steel cover is compatible with all materials
- ◆ Suction and return tubes benefits suitable for re-circulating

